



← Disassembly dimension →

Type		AL Dairy									AXL Dairy									
AL	AXL	Ltr/rev	DIN			ANSI			E	H	ØA	ØB	D	ØC	ØB	D	E	H	F	G
150		2,5	150	240	8xØ23	285	241,3	8xØ22,2	12	110								280	140	
175	200	5,5	175	270	8xØ23	315	-	-	14	130	200	295	8xØ23	343	298,4	8xØ22,2	14	165	330	165
200	250	10,5	200	295	8xØ23	343	298,4	8xØ22,2	14	160	250	350	12xØ23	406	361,9	12xØ25,4	16	197,5	390	195
250	300	19	250	350	12xØ23	406	361,9	12xØ25,4	16	190	300	400	12xØ23	483	431,8	12xØ25,4	21	222,5	450	225
300	350	34	300	400	12xØ23	483	431,8	12xØ25,4	21	225	350	460	16xØ23	530	476,2	12xØ28,6	21	225	540	270
350		58	350	460	16xØ23	530	476,2	12xØ28,6	26	270								660	330	

Type		K	L	M	N	NN	O	U	V	X**	Y	Z*	AA	BB	CC	DD	EE	FF	GG	ZZ
150		521	72	151	146	-	100	3xM6	4xM10	¼" (Ø10)	40	UNEF 1½"	37,1	37,1	52,5	8	30	33	35	532
175	200	561	72	149	190	-	100	3xM6	4xM10	¼" (Ø10)	53	UNEF 1½"	37,1	37,1	52,5	8	30	33	35	592
200	250	646	84	166	234	-	125	3xM8	4xM12	¼" (Ø10)	65	UNEF 1½"	55,4	32	64	10	32	35	43	692
250	300	696	84	166	284	142	125	3xM8	6xM12	¼" (Ø10)	75	UNEF 1½"	55,4	32	64	10	32	35	43	767
300	350	804	80	185	360	180	125	3xM10	6xM12	¼" (Ø10)	95	UNEF 1½"	73,6	85	42,5	10	38	41	44	915
350		874	80	190	420	210	125	3xM10	6xM12	¼" (Ø10)	112	UNEF 1½"	73,6	85	42,5	10	38	41	44	1000

\* Standard pre-drilled for cast iron | Standaard voorgeboord bij gietijzer | Standard gebohrt in Gußeisen | Standard percé pour fonte | Estándar pre-taladrado para fundición de Fe | Standard preforato per ghisa | Standardowo otwory w żelazie | Предварительно изготовленные отверстия стандартны для чугуна

\*\* Air purge connection | Aansluiting luchtdichting | Luftspülanschluss | Connexion insufflation d'air | Entrada de aire de sellado | Ingresso aria di fl ussaggio | Złącze powietrza płuczącego | Подключение продувки во вздухом